



Benefits of Rain Barrels:

- Rain water is free from added chemicals
 - Water conservation
 - Reduction and control of water run-off
 - Convenience
 - Save money
 - Self-satisfaction
-



NEWPORT NEWS
Waterworks
DEPARTMENT
Newport News Waterworks
(757)926-1000



Newport News Dept. of
Public Works Recycling
Office
(757)269-2700

 **Virginia Cooperative Extension**
Virginia Tech • Virginia State University
www.ext.vt.edu
Virginia Cooperative Extension is a part of the Virginia State University system. It is an equal opportunity institution. All programs and services are available to all people without regard to race, color, sex, religion, national origin, or age. For more information, contact your local extension office.

(757) 591-4838


**The
Mariners'
Museum
and Park**
(757) 591-7741



Save Water, Save Money

MAKE A RAIN BARREL!




Suggested Parts

- 1—55 gal. barrel, once used to transport food (pickles, olives), preferably with removable lid
- 1—½” non-kink male bibb
- 1—¾” Hose barb adapter
- 1—hose gaskets
- 1—½” conduit lock nut (opt.)
- 1—6” round drain grate
- 1—7” round worm gear clamp
- Waterproof or marine glue
- Screening (nylon mesh is best)

Suggested Assembly

- Cut a 6” hole in lid or top. Rough edges may be smoothed with a file.
- Drill a ½” or slightly smaller hole near bottom of barrel.
- Cut and wrap screen material around top of grate; hold in place using clamp, and place in hole of lid.
- Work hose gasket around male end of bibb, add glue around end of bibb, and hand screw into hole at bottom until snug.
- As an option, a conduit lock nut and gasket may be screwed on bibb from inside of barrel. Glue may also be added there. Allow 24 hours to cure.



Further Notes

- **Gutter downspout will likely need to be cut.** Flexible gutter connections can be used to connect downspout to barrel.
- **Barrel should be placed under spout at lowest point of house.**
- **Rinse barrel thoroughly before collecting rain water.** (Some containers had salt-based preservatives in them that could be harmful to plants)
- **A jigsaw, hole saw, Rotozip saw or handsaw may be used to cut large 6” hole in lid.**
- **Hole in lid for drain should be small enough for drain to be snug but easily removed for cleaning.**
- **Small holes may be drilled around inside of lid to prevent water from accumulating.**
- **An overflow hole may be drilled near top side of barrel.** Attach a plastic male hose adapter to allow for overflow or to attach to another rain barrel. (See picture of painted rain barrels.)
- **In extreme freezing conditions, water should be drained from barrels.**
- **Barrel should be placed on a stand or 2 cinder blocks 16-20 inches high.** This helps with the gravity flow of water or for attaching a water hose.